



4000[®]
UNIVERSAL TRACTOR
HYDRAULIC FLUID



Poly 7[®]
High Temp



GLOBALTRANS[®]
Full Synthetic Multi-Vehicle ATF



Syn Gold
Full Synthetic
Motor Oil



COMMERCIAL / INDUSTRIAL PRODUCT CATALOG



MOTOR OILS

SYN CLEAN®

SynClean® extends engine life, significantly reduces engine wear, resists thermal breakdown, and outperforms conventional engine oils in engine cleanliness, fuel economy, and protection between moving parts. Meets new passenger car engine warranty requirements.



SYNGOLD®

SynGold® full synthetic motor oils are uniquely designed to help provide outstanding levels of fuel economy performance, cleaning power and engine protection, even during longer oil change intervals. SynGold® is proven to significantly reduce wear and viscosity breakdown because of its advancements in oil technology. SynGold® full synthetic motor oils are approved for use in General Motors, Ford and Chrysler flex-fuel vehicles using either gasoline or E-85. Suitable for use in all Dexos 1 applications.



Part #	Description	Size
4230H	5W20 Synthetic Blend Motor Oil SN/GF-5	12 / 1 Qt.
4230AN	5W20 Synthetic Blend Motor Oil SN/GF-5	55 Gal.
4231H	5W30 Synthetic Blend Motor Oil SN/GF-5	12 / 1 Qt.
4231AN	5W30 Synthetic Blend Motor Oil SN/GF-5	55 Gal.
4232H	10W30 Synthetic Blend Motor Oil SN/GF-5	12 / 1 Qt.
4232AN	10W30 Synthetic Blend Motor Oil SN/GF-5	55 Gal.
4428AN	0W-30 Full Synthetic Motor Oil SN/GF-5	55 Gal.
4429AN	0W-20 Full Synthetic Motor Oil SN/GF-5	55 Gal.
4430H	5W-20 Full Synthetic Motor Oil SN/GF-5	6 / 1 Qt.
4430AN	5W-20 Full Synthetic Motor Oil SN/GF-5	55 Gal.
4431H	5W-30 Full Synthetic Motor Oil SN/GF-5	6 / 1 Qt.
4431AN	5W-30 Full Synthetic Motor Oil SN/GF-5	55 Gal.
4003A	Non-Detergent 10W-10	55 Gal.
4003U	Non-Detergent 10W-10	2/2.5 Gal.
4004U	Non-Detergent 20W-20	2/2.5 Gal.
4004H	Non-Detergent 20W-20	12/1 Qt.
4005A	Non-Detergent 30	55 Gal.
4005U	Non-Detergent 30	55 Gal.
4005H	Non-Detergent 30	12/1 Qt.
4033H	Heavy Duty 30 SN	12/1 Qt.
4030A	High Mileage 10W-40 SN	55 Gal.
4030H	High Mileage 10W-40 SN	12/1 Qt.
4025H	2-Cycle Engine Oil	12/1 Qt.
4025J	2-Cycle Engine Oil	24/8 Oz.
4425V	2-Cycle Engine Oil	24/2.6 Oz.
4115L	2-Cycle Power Equipment Oil	48/2.56 Oz.
4115J	2-Cycle Power Equipment Oil	48/6.4 Oz.
4115K	2-Cycle Power Equipment Oil	12/12.8 Oz.
4115N	2-Cycle Power Equipment Oil	4/1 Gal.
4115D	2-Cycle Power Equipment Oil	5 Gal.
4115AC	2-Cycle Power Equipment Oil	55 Gal.

FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT WWW.CHAMPIONBRANDS.COM

HEAVY DUTY 30 OIL



CHAMPION SUPER GRADE HEAVY DUTY MOTOR OIL is designed and licensed to meet API service category SN specifications where applicable. Meets SAE specifications and meets both domestic and foreign OEM warranty requirements for use in gasoline and turbo charged gasoline engines.

HIGH MILEAGE OILS



CHAMPION HIGH MILEAGE MOTOR OILS are formulated to protect your vehicle's engine by boosting seal conditioners, cleaning agents and friction modifiers while resisting thermal breakdown. Working together, these elements maximize life and sustain the performance of engines with more than 75,000 miles. Meets, or exceeds, API SN, SM, and SL/CF.

2-CYCLE OILS

2-CYCLE ENGINE OIL



CHAMPION 2-CYCLE ENGINE OIL is specially blended for use in a wide range of 2 cycle engines, including chain saws. It will improve performance while reducing engine wear, carbon, and spark plug fouling. Can be used with oxygenated/gasohol fuels. Meets, or exceeds API TC.



2-CYCLE POWER EQUIPMENT OIL

CHAMPION 2-CYCLE POWER EQUIPMENT OIL is a premium quality, clean burning oil that meets and exceeds JASO FD and ISO-L-EGD performance levels. These oils are produced with the highest quality additives available to assure performance and protection for all equipment needs in high RPM, high temperature, air-cooled 2 cycle engines.

DIESEL MOTOR OILS

Part #	Description	Size
4036A	Premium Heavy Duty 10W-10	55 Gal.
4036U	Premium Heavy Duty 10W-10	2/2.5 Gal.
4038A	Premium Heavy Duty 30	55 Gal.
4038U	Premium Heavy Duty 30	2/2.5 Gal.
4039A	Premium Heavy Duty 40	55 Gal.
4039U	Premium Heavy Duty 40	2/2.5 Gal.
4040A	Premium Heavy Duty 50	55 Gal.
4152A	Premium Heavy Duty 15W-40 CJ-4/SN	55 Gal.
4152U	Premium Heavy Duty 15W-40 CJ-4/SN	2/2.5 Gal.
4152N	Premium Heavy Duty 15W-40 CJ-4/SN	4/1 Gal.
4160A	All-Fleet T 10W-30 CJ-4/SM	55 Gal.
4160H	All-Fleet T 10W-30 CJ-4/SM	12/1 Qt.
4158A	All-Fleet T 15W-40 CJ-4/SN	55 Gal.
4158U	All-Fleet T 15W-40 CJ-4/SN	2/2.5 Gal.
4158N	All-Fleet T 15W-40 CJ-4/SN	4/1 Gal.
4158H	All-Fleet T 15W-40 CJ-4/SN	12/1 Qt.
4173A	All-Fleet T Heavy Duty 5W-40 CJ-4/SM	55 Gal.
4173D	All-Fleet T Heavy Duty 5W-40 CJ-4/SM	5 Gal.

PREMIUM HEAVY DUTY

MONO-GRADE SERIES:

Champion Premium Heavy Duty Mono-Grade Series diesel engine oils are an excellent and economical choice for engines which specify API CF-2 oils, or that specify API CF/SF or earlier specifications which can no longer be licensed under API.

HEAVY DUTY 15W-40:

Champion Premium Heavy Duty 15W-40 diesel engine oil is made using select hydro-cracked base stocks and meet current OEM warranty requirements for engines with advanced emissions control systems including diesel particulate filters (DPF), exhaust gas recirculation (EGR) and selective catalytic reduction (SCR).



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM

ALL-FLEET T[®] OILS



ALL-FLEET T[®]

CHAMPION ALL-FLEET T[®] premium multi-grade, heavy-duty motor oils are formulated for heavy-duty workloads of diesel engines. They meet and exceed most diesel engine manufacturers requirements, including Caterpillar, Detroit Diesel, Cummins and Volvo.

CHAMPION ALL-FLEET T[®] Motor Oils are blended with hydrocracked, severely hydrotreated base oils which are virtually free of contaminants, enhancing the performance of the finished oil. OEM Certified for extended service drain. Best in class TBN retention (alkaline reserve), ensuring protection required for new and pre-2007 emission compliant engines.



TRANSMISSION FLUIDS

Part #	Description	Size
4355H	Universal Automatic Transmission Fluid	12/ 1 Qt.
4355A	Universal Automatic Transmission Fluid	55 Gal.
4355D	Universal Automatic Transmission Fluid	5 Gal.
4355U	Universal Automatic Transmission Fluid	2/2.5 Gal.
4355N	Universal Automatic Transmission Fluid	4/1 Gal.
4357H	GlobalTrans Synthetic M-V ATF	6/1 Qt.
4357A	GlobalTrans Synthetic M-V ATF	55 Gal.
4357D	GlobalTrans Synthetic M-V ATF	5 Gal.
4313A	TO-4 Power Transmission Fluid 10W-10	55 Gal.
4345A	TO-4 Power Transmission Fluid 30	55 Gal.
4345D	TO-4 Power Transmission Fluid 30	5 Gal.
4287A	Super Grade SynBlend Torque Fluid 10W-40	55 Gal.
4287U	Super Grade SynBlend Torque Fluid 10W-40	2/2.5 Gal.

UNIVERSAL AUTOMATIC TRANSMISSION FLUID

CHAMPION UNIVERSAL AUTOMATIC TRANSMISSION FLUID is a multi-functional power transmission fluid providing excellent anti-shudder, anti-friction, and high and low temperature protection. It is recommended for use in all American and foreign automatic transmissions requiring the performance requirements of Ford Mercon®, GM Dexron® III, Allison C-4, Cat TO-2, and Ford Type H, Ford TASA and CJ specifications.



SUPER GRADE SYNBLEND TORQUE FLUID 10W-40

CHAMPION SUPER GRADE TORQUE FLUID is a hydrostatic transmission fluid used in most automatic and hydrostatic transmissions. It has low viscosity, low pour point, and high VI, to insure excellent fluidity characteristics over a wide temperature range. This allows it to be used with complete confidence over extreme temperature ranges while maintaining superior low speed characteristics without sticking, slipping, or chattering. It also has the proper frictional and anti-wear properties necessary for high speed operations while minimizing wear. It is particularly suited for the variable-volume piston pumps used in hydrostatic transmission systems. It can also be used as an A.W. hydraulic fluid. Meets or exceeds specifications for Cat TO-4M.



GLOBALTRANS® SYNTHETIC ATF

CHAMPION GLOBALTRANS® FULL SYNTHETIC MULTI-VEHICLE automatic transmission fluid delivers superior performance in low-temperature flow, wear protection, frictional stability and resistance to thermal breakdown and is made with a 100% synthetic base fluid chosen for superior resistance to oxidation and viscosity change. This product has a highly shear stable cold flow viscosity control additive for superior resistance to viscosity change over thousands of miles. Has optimized friction control additives that not only prevent slip and shudder, for smooth shifting, but are more durable than many other competing brands. It meets or exceeds Mercon V and Allison TES-295 specifications.

TO-4 TRANSMISSION FLUID

CHAMPION TO-4 TRANSMISSION FLUID is our superior hydraulic, transmission and final drive lubricant specifically formulated for use in Caterpillar equipment where a TO-4 fluid is specified. It is designed to give the ultimate protection and performance in power shift, hydrostatic transmissions, torque converters, and provide cleanliness, friction modification and stability. These formulations have extended component life in these systems. In addition to meeting Caterpillar TO-4 requirements, they surpass Allison C-4 and API GL-3 specifications. They increase service life and performance in other applications specifying Allison C-2 or C-3 and Caterpillar TO-2.



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM



HYDRAULIC OILS

R&O HYDRAULIC FLUIDS

CHAMPION R&O HYDRAULIC FLUID series includes our general purpose lubricants made from paraffinic base stocks. These fluids are excellent for use as circulating oils or process oil and in use with pumps not requiring AW oils. Often used as a general purpose industrial lubricant.



SUPER GRADE AW/R&O FLUIDS

CHAMPION SUPER GRADE AW R&O HYDRAULIC FLUID series are high performance anti-wear hydraulic oils designed to satisfy a wide range of hydraulic equipment requirements. They meet the stringent requirements of severe hydraulic systems using high pressure, high output pumps as well as handling the critical requirements of other hydraulic system components such as close clearance servo-valves and the high accuracy numerically controlled (NC) machine tools. Meets or exceeds specifications for Parker-Haniffin HF-0. *Typical 5,000 hour life.



*Typical life is an average that does not constitute a specification.

Part #	Description	Size
4017A	Hydraulic R&O ISO 22	55 Gal.
4018A	Hydraulic R&O ISO 32	55 Gal.
4018D	Hydraulic R&O ISO 32	5 Gal.
4018U	Hydraulic R&O ISO 32	2/2.5 Gal.
4018N	Hydraulic R&O ISO 32	4/1 Gal.
4019A	Hydraulic R&O ISO 46	55 Gal.
4019D	Hydraulic R&O ISO 46	5 Gal.
4019U	Hydraulic R&O ISO 46	2/2.5 Gal.
4192A	Hydraulic R&O ISO 68	55 Gal.
4192D	Hydraulic R&O ISO 68	5 Gal.
4192U	Hydraulic R&O ISO 68	2/2.5 Gal.
4245A	Super Grade AW/R&O 32 - Typical 5,000 hour life	55 Gal.
4180A	Super Grade AW/R&O 46 - Typical 5,000 hour life	55 Gal.
4181A	Super Grade AW/R&O 68 - Typical 5,000 hour life	55 Gal.
4178A	Super Grade AW/R&O 100 - Typical 5,000 hour life	55 Gal.
4212A	Super Grade AW/R&O 150 - Typical 5,000 hour life	55 Gal.
4266A	Quantum A/S Hydraulic 3200 MV - Typical 7,000 hour life	55 Gal.
4266D	Quantum A/S Hydraulic 3200 MV - Typical 7,000 hour life	5 Gal.
4267A	Quantum A/S Hydraulic 4600 MV - Typical 7,000 hour life	55 Gal.
4267D	Quantum A/S Hydraulic 4600 MV - Typical 7,000 hour life	5 Gal.
4268A	Quantum A/S Hydraulic 6800 MV - Typical 7,000 hour life	55 Gal.
4268D	Quantum A/S Hydraulic 6800 MV - Typical 7,000 hour life	5 Gal.
4318A	Quantum AW ISO 32 - Typical 7,000 hour life	55 Gal.
4319A	Quantum AW ISO 46 - Typical 7,000 hour life	55 Gal.
4320A	Quantum AW ISO 68 - Typical 7,000 hour life	55 Gal.
4320D	Quantum AW ISO 68 - Typical 7,000 hour life	5 Gal.
4327A	Quantum AW ISO 100 - Typical 7,000 hour life	55 Gal.
4321A	Quantum Ashless R&O 32 - Typical 10,000+ hour life	55 Gal.
4323A	Quantum Ashless R&O 46 - Typical 10,000+ hour life	55 Gal.
4322A	Quantum Ashless R&O 68 - Typical 10,000+ hour life	55 Gal.
4329A	Quantum Ashless R&O 150 - Typical 10,000+ hour life	55 Gal.
4326A	Quantum Ashless R&O 220 - Typical 10,000+ hour life	55 Gal.

QUANTUM AW MULTI-VISCOSITY HYDRAULIC FLUIDS

CHAMPION QUANTUM series includes our anti-wear hydraulic and rust and oxidation fluids made from premium Group II base stocks in combination with advanced additive protection systems. Available in mono-grades (Quantum AW R&O), and multi-grades (Quantum All Season), these series provide the best protection for all vane, piston, gear hydraulic and compressor pumps. Recommended for surface mining cranes, shovels and walking cranes hydraulic systems, cherry pickers, farm tractor implements, backhoes, loaders, hydraulic lifts and hydraulic systems on dump trucks, motor graders, bulldozers, and forklifts. Meets or exceeds Parker-Haniffin HF-0. *Typical 7,000 hour life.



TRACTOR FLUIDS

Part #	Description	Size
4000A	4000 Premium Tractor Hydraulic Fluid	55 Gal.
4000D	4000 Premium Tractor Hydraulic Fluid	5 Gal.
4000U	4000 Premium Tractor Hydraulic Fluid	2/2.5 Gal.
4000N	4000 Premium Tractor Hydraulic Fluid	4/1 Gal.
4011A	Hydraulic Transmission (HyTran)	55 Gal.
4011U	Hydraulic Transmission (HyTran)	2/2.5 Gal.
4010U	JDT 303 30	2/2.5 Gal.
4101A	AC Hydraulic 803 30	55 Gal.



4000® PREMIUM TRACTOR HYDRAULIC FLUID

CHAMPION 4000® PREMIUM TRACTOR HYDRAULIC FLUID is our premium quality UTTO, specially formulated for over 40 years to "Keep Farmers in the Field". Champion's hydrofinished base fluids combined with "OEM preferred" additive technology makes Champion 4000® the most universally diverse fluid available for use in farm tractors and implements, fork lift trucks, pavement rollers, loaders, backhoes, bulldozers, tractors, ditchers, 4x4 ATV with wet brake differentials, and lawn tractors and golf course mowers with hydrostatic transmissions. It delivers exceptional performance in today's power train transmissions, drive axles, clutches, PTO's, hydraulic systems, and honors more warranties than any other tractor fluid in the market.

CHAMPION 4000® PREMIUM TRACTOR HYDRAULIC FLUID offers friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and deep cold pumpability, all optimally balanced to provide extended clutch life and maximum drawbar loading in a wide range of ambient temperatures.



Meets and Exceeds NEW
TRACTOR WARRANTY
Requirements Including
J20C



HYTRAN (HYDRAULIC TRANSMISSION FLUID)

CHAMPION HY-TRAN is formulated using the highest quality paraffin base stocks available combined with the latest "state of the art" additives to produce a truly outstanding HY-TRAN with rust and oxidation inhibitors to protect wet brakes from corrosion, excellent cold flow properties, and power train friction protection. Meets or exceeds MS-1204, MS-1205, MS-1206 (Powergard PTF), MS-1207 Hy-Trans Plus, MS-1210, and maintains any existing warranties.

FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM



GEAR OILS

Part #	Description	Size
4041A	All Purpose (GL-1) GL-3 SAE 90 Gear Lube	55 Gal.
4041U	All Purpose (GL-1) GL-3 SAE 90 Gear Lube	2/2.5 Gal.
4041N	All Purpose (GL-1) GL-3 SAE 90 Gear Lube	4/1 Gal.
4042U	All Purpose (GL-1) GL-3 SAE 140 Gear Lube	2/2.5 Gal.
4120A	Heavy Duty AP GL-5 80W-90 Gear Lube	55 Gal.
4120C	Heavy Duty AP GL-5 80W-90 Gear Lube NR	16 Gal.
4120D	Heavy Duty AP GL-5 80W-90 Gear Lube	5 Gal.
4120U	Heavy Duty AP GL-5 80W-90 Gear Lube	2/2.5 Gal.
4120N	Heavy Duty AP GL-5 80W-90 Gear Lube	4/1 Gal.
4120H	Heavy Duty AP GL-5 80W-90 Gear Lube	12/1 Qt.
4157A	Heavy Duty AP GL-5 85W-140 Gear Lube	55 Gal.
4157C	Heavy Duty AP GL-5 85W-140 Gear Lube	16 Gal.
4157U	Heavy Duty AP GL-5 85W-140 Gear Lube	2/2.5 Gal.
4157H	Heavy Duty AP GL-5 85W-140 Gear Lube	12/1 Qt.
4015U	Ford/MF Tractor 90	2/2.5 Gal.
4269A	Quantum MV Gear Lube 150	55 Gal.
4068A	Industrial EP Gear Lube ISO 68	55 Gal.
4069A	Industrial EP Gear Lube ISO 150	55 Gal.
4070A	Industrial EP Gear Lube ISO 220	55 Gal.
4071A	Industrial EP Gear Lube ISO 320	55 Gal.
4076A	Industrial EP Gear Lube ISO 460	55 Gal.
4077A	Industrial EP Gear Lube ISO 680	55 Gal.
4082AN	SynBlend EP Gear Lube 150	55 Gal.
4314AN	HTS Synthetic Gear Lube 75W-90	55 Gal.
4314D	HTS Synthetic Gear Lube 75W-90	34 Lbs.
4314C	HTS Synthetic Gear Lube 75W-90	16 Lbs.
4315AN	HTS Synthetic Gear Lube 80W-140	55 Gal.
4315D	HTS Synthetic Gear Lube 80W-140	34 Lbs.
4316AN	HTS Synthetic CD 50	55 Gal.
4316D	HTS Synthetic CD 50	34 Lbs.
4131AN	SynGold EP Gear Lube 68 NR	55 Gal.
4094AN	SynGold EP Gear Lube 100	55 Gal.
4095AN	SynGold EP Gear Lube 150	55 Gal.
4106AN	SynGold EP Gear Lube 220	55 Gal.
4098AN	SynGold EP Gear Lube 320	55 Gal.
4099AN	SynGold EP Gear Lube 460	55 Gal.
4102AN	SynGold EP Gear Lube 680	55 Gal.

HTS SYNTHETIC GEAR LUBE

CHAMPION HTS Gear Lubes are premium, fully synthetic extreme pressure automotive gear lubricants designed to meet the challenges of modern light-duty and heavy-duty axle differentials. Longer service intervals, more power transfer density, smaller oil volumes and limited air cooling place exceptional demands on today's axles. Only an exceptional lubricant should be trusted to protect your equipment. Meets or exceeds API GL-5 specs.



ALL PURPOSE (GL-1) GL-3 GEAR LUBE

CHAMPION GL-3 ALL PURPOSE GEAR LUBE is a high quality, moderate duty, extreme pressure, all purpose gear lube for use in automotive, agricultural and industrial applications. For use where the manufacturer specifies AGMA EP, AGMA 9005-D94, US STEEL (AIST) 224, Cincinnati Milacron, Extreme Pressure, or GL-3 gear lube.



HEAVY DUTY ALL PURPOSE GL-5 GEAR LUBE

CHAMPION HD ALL PURPOSE GL-5 GEAR LUBES are our general purpose, high VI multi-viscosity gear lubes manufactured from the finest quality select paraffin base stocks available and blended with premium additives to exacting specifications. These lube oils provide exceptional cold flow properties with high adherence to gears even under high speed, giving quicker lubrication under the most severe weather conditions.



FORD/MF TRACTOR 90 TRANSMISSION LUBE

CHAMPION FORD TRACTOR TRANSMISSION is a high quality moderate duty, extreme pressure, all purpose gear lube specifically designed for use in older Ford tractors where a common reservoir is used for transmission, differential and hydraulic pump. It can also be used in automotive, industrial and other agricultural applications and meets or exceeds M4864B, API GL-3, Cincinnati Milacron, AGMA 9005-D94, US Steel (AIST) 224, and maintains any existing warranties.



INDUSTRIAL EP GEAR LUBE

CHAMPION INDUSTRIAL EP GEAR series are highly purified industrial gear lubricants made with the finest additives providing excellent lubrication protection under extreme pressure conditions. Top-tier solvent-refined, paraffinic base stocks are employed to provide the necessary oxidation control under the most difficult conditions far exceeding U.S. Steel (AIST) 224, AGMA 9005 EP, and Cincinnati Machine (CM) gear lubricant performance requirements.



SYNGOLD® EP GEAR LUBE

CHAMPION SYNGOLD EPG series includes our premium universal industrial and automotive gear lubricants designed to maximize the cost and performance benefits of using synthetic lubricants. SynGold EP Gear Lube is recommended for extended drain and the multi-viscosity fluids promote universal versatility with high shear rate protection. This product is formulated to provide premium thermal and oxidation protection against excessive contact wear, wide pressures ranges, and corrosion. Universally compatible with all mineral based and synthetic fluids. Meets or exceeds AGMA 9005EP and AIST224 specifications.



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM

INDUSTRIAL OILS

VI OIL IMPROVER

CHAMPION VI OIL TREATMENT improves oil viscosity and increases oil pressure, power and compression. Oil Improver also decreases oil consumption and engine wear. It forms a film which coats and protects vital engine parts, reduces friction and increases power. Add one pint of Champion Oil Treatment to four to five quarts of oil for top performance and increased engine life.



WHITE LUBE OIL

CHAMPION WHITE LUBE OIL is a food-grade lubricant for use in a variety of applications where a USDA H2 is required. It is a white mineral base oil providing rust and oxidation inhibition and offers excellent anti-wear protection. It is recommended for hydraulic systems and gear systems requiring food-grade oils. It is also a reduced environmental impact lubricant and inherently biodegradable by OECD 203 1-12 Test Method. It performed well in both aqueous acute toxicity tests and "ultimate" biodegradability tests.



HEAVY DUTY COMPRESSOR OIL

CHAMPION HEAVY DUTY COMPRESSOR OIL is designed for use in single-stage reciprocating compressors, two-stage reciprocating compressors, multi-stage reciprocating compressors, and rotary screw compressors where the manufacturers recommend this viscosity grade. It possesses low foaming tendency, coupled with a select additive package which enhances lubricity, protects against rust and oxidation, protects against harmful sludge, varnish deposits and wear.



SUPER GRADE WAYLUBE OIL

CHAMPION SUPER GRADE PREMIUM WAY SLIDE LUBRICANTS lubricate machine tool ways, slides and guides. Available in two viscosity grades, they are made by blending high quality base oils with friction-modifying additives and other chemical agents to give them greater load carrying qualities, better anti-wear characteristics and increased adhesiveness.



QUANTUM HEAT TRANSFER OIL 32

CHAMPION QUANTUM HEAT TRANSFER OIL is designed for use in both open and closed systems using a petroleum medium for heat transfer. It is formulated from the finest paraffinic base oil stocks and blended with high tech additives to give it excellent stability, low volatility, good thermal and oxidation stability. CHAMPION HEAT TRANSFER FLUID can be used in open systems up to 375 ° F and closed systems up to 600 ° F.



AIR TOOL OIL

CHAMPION AIR TOOL OILS are designed to lubricate pneumatic (air) driven tools of all types. They possess extreme pressure characteristics for longer tool life under the most demanding conditions. They also contain rust and oxidation additives for protection from moisture. The naturally high viscosity index provides protection for operation during cold temperatures as well as hot.



Part #	Description	Size
4073AN	Smoke Oil	55 Gal.
4083AN	VI Oil Improver NR	55 Gal.
4083D	VI Oil Improver	5 Gal.
4243AN	White Lube Oil 22 HVI	55 Gal.
4294AN	Diesel-Flo K HM NR	55 Gal.
4139A	HD Compressor Oil	55 Gal.
4139H	HD Compressor Oil	12/1 Qt.
4239A	SG Waylube ISO 68	55 Gal.
4238A	SG Waylube ISO 150	55 Gal.
4241A	SG Waylube ISO 220	55 Gal.
4235A	SG Quenching Oil	55 Gal.
4218A	Quantum HTO 32	55 Gal.
4196A	SG Cut Fluid	55 Gal.
4194A	SG Cut Fluid - Soluble	55 Gal.
4171A	Drawing RP Fluid Heavy	55 Gal.
4248A	SG Rock Drill ISO 150	55 Gal.
4251A	SG Rock Drill ISO 220	55 Gal.
4067V	Air Tool Oil- Light	12/4 Oz
4072A	Air Tool Oil	55 Gal.
4213A	RP Stamp Oil - Light	55 Gal.
4151A	Mineral Seal Oil	55 Gal.
4103A	Form Oil	55 Gal.
4224A	RP Machine Oil	55 Gal.
4244A	SG Penetrating Oil	55 Gal.
4128A	Sand Green Oil	55 Gal.
4328AN	Syntinel ESL UL 15 - Typical 10,000+ hour life	55 Gal.
4331AN	Syntinel ESL UL 32 - Typical 10,000+ hour life	55 Gal.
4333AN	Syntinel ESL UL 46 - Typical 10,000+ hour life	55 Gal.
4333D	Syntinel ESL UL 46 - Typical 10,000+ hour life	5 Gal.
4335AN	Syntinel ESL UL 68 - Typical 10,000+ hour life	55 Gal.
4337AN	Syntinel ESL UL 150 - Typical 10,000+ hour life	55 Gal.

RP MACHINE OIL

CHAMPION SUPER GRADE RP MACHINE OIL is for customers who require better rust and corrosion protection on metal surfaces exposed to outside weather conditions. Champion Super Grade RP Machine Oil is a highly effective non-staining preservative fluid for use on sheet, coiled, or wire rope alloys.




SYNTINEL ESL SERIES OIL

CHAMPION SYNTINEL ESL synthetic, high performance hydraulic oils are our top-tier hydraulic and industrial oils designed for the most demanding operating conditions. Syntinel oils protect your hydraulic equipment even under the harshest conditions and shows exceptional performance as steel mill and paper machine oil. Excellent service fluid for use where an HF-0 oil is specified. *Typical 10,000 hour life.



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM

*Typical life is an average that does not constitute a specification.



GREASE PRODUCTS

Part #	Description	Size
4052C	Amber Lithium Grease	120 Lbs.
4052D	Amber Lithium Grease	35 Lbs.
4052T	Amber Lithium Grease	40/14 oz.
4051C	Moly EP Grease	120 Lbs.
4051D	Moly EP Grease	35 Lbs.
4051T	Moly EP Grease	40/14 oz.
4050T	Poly 7® High Temp Grease	40/14 oz.
4050A	Poly 7® High Temp Grease	400 Lbs.
4050C	Poly 7® High Temp Grease	120 Lbs.
4050D	Poly 7® High Temp Grease	35 Lbs.

MOLY EP GREASE

CHAMPION MOLY E.P. GUN GREASE is a high quality lithium grease containing Molybdenum Disulfide. It is recommended for use in industrial, agricultural and automotive applications, as well as specialized areas. CHAMPION MOLY E.P. GUN GREASE contains inhibitors to prevent rust, oxidation, and corrosion. This lithium grease provides low friction and resistance to water washout.

Recommended for the following applications:

- Farm Equipment
- Industrial Equipment
- Mining Equipment
- Chassis Lubrication Points
- King Pins/Ball Joints
- Fifth Wheels



AMBER LITHIUM GREASE

CHAMPION AMBER LITHIUM is a light amber colored lithium grease with good load carrying, rust and oxidation protection and corrosion resistant characteristics. It has good pumpability and low temperature properties. It is recommended for general purpose lubrication for automotive, agricultural and industrial applications. It is available in NLGI Grade #2.

Recommended for the following applications:

- Farm Equipment
- Industrial Equipment
- Mining Equipment
- Chassis Lubrication Points
- King Pins/Ball Joints
- Fifth Wheels



POLY 7® HIGH TEMP GREASE

CHAMPION BRANDS POLY 7® GUN GREASE is a high-temp, lithium complex, all weather grease, meeting the requirements of NLGI GC-LB for automotive wheel bearing and chassis lubrication. Continuously coats all surfaces to prevent fretting, corrosion, and increases bearing life. Can be used in multiple applications and is recommended for heavy duty trucks, fleet, farm, marine and industrial equipment where an AGMA or NLGI #2 heavy duty grease is required.

A special additive "A-7" gives CHAMPION POLY-7® increased lubrication and delivers excellent oxidation, adhesion, and pumpability characteristics. It resists moisture and water washout. CHAMPION POLY-7® is an all weather grease meeting the requirements of NLGI GC-LB for automotive wheel bearing and chassis lubrication.



Poly 7®

High Temp



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT
WWW.CHAMPIONBRANDS.COM

AUTOMOTIVE CHEMICALS



BRAKE CLEANER

Champion Hi-Tech Brake Cleaner removes grease, oil, brake fluid and other contaminants from disc and drum brake components without leaving any residue. Cleans without disassembly. Helps stop brake squealing and can improve braking performance. Non-flammable, and can be used to clean any automotive electrical components. Does not contain silicones, leaves no residue.

4126P - 12 / 19 oz. (Is compliant for sale in North America EXCEPT for California, New Jersey and Billings, Montana)



NON-CHLORINATED BRAKE CLEANER

Removes grease, oil, brake fluid and other contaminants from disc and drum brake components instantly. Cleans without disassembly. Helps stop brake squealing and can improve braking performance. Leaves no residue.

4125I - 12 / 15 oz. (Is compliant for sale in North America, but specially formulated to meet CARB VOC requirements for California; EXCEPT for the South Coast Air Quality Management District (SCAQMD) Rule 1171)



NON-CHLORINATED FAST DRY BRAKE GUARD

Meets all current VOC regulations for California and other OTC States. Removes grease, oil, brake fluid and other contaminants from disc and drum brake components instantly. Cleans without disassembly. Helps stop brake squealing and can improve braking performance. Leaves no residue.

4221I - 12 / 12.5 oz. (Is compliant for sale in North America, but specially formulated to meet CARB VOC requirements for California; EXCEPT for the South Coast Air Quality Management District (SCAQMD) Rule 1171)

BRAKE CLEANERS		Pkg.
4126P	Professional Brake Parts Cleaner	12/19 oz.
4125I	Professional Non-Chlor Brake Cleaner	12/15 oz.
4221I	Fast Dry Non-Chlor Brake Cleaner	12/12.5 oz.
4125D	Non-Chlorinated Brake Cleaner	5 gal.
4125AN	Non-Chlorinated Brake Cleaner	55 gal.



HEAVY DUTY ENGINE DEGREASER

A solvent based formula that is a remarkably fast engine degreaser. It will remove grease, sludge, dirt, and tar from an engine within minutes. Simply spray on and hose off. Ideal for cleaning lawn mowers, marine engines, truck engines, motorcycle engines, and garage floors.

4123I - 12 / 16 oz. (Is compliant for sale in North America)



CARBURETOR CLEANER

Restore carburetor performance by removing gum, varnish, carbon deposits and dirt build-up. Cleans and frees automatic chokes, carburetor linkage, fuel injection intake systems, manifold heat controls and PCV smog valve.

4121K - 12 / 11 oz. (Is compliant for sale in North America, but specially formulated to meet CARB VOC requirements for California; EXCEPT for the South Coast Air Quality Management District (SCAQMD) Rule 1171)



RX-454 PENETRANT

This amazing liquid spray tool penetrates, lubricates, and stops rust. Makes repairs work easier whenever trouble is caused by corrosion, moisture, dirt or friction. Great for drying wet ignition systems, silencing squeaks, and will not harm rubber, plastics or painted surfaces.

4244M - 12 / 9 oz. (Is compliant for sale in North America @ 48.9% VOC)

AEROSOLS		Pkg.
4121K	Carburetor Cleaner	12/11 oz.
4121KC	Carb Cleaner (CA compliant)	12/13 oz.
4123I	Engine Degreaser	12/16 oz.
4244M	RX 454 Penetrant	12/9 oz.
4303P	Wipe-R-Clean Glass Cleaner	12/19 oz.

ANTIFREEZE



CHAMPION PERMANENT ANTIFREEZE

CHAMPION BRANDS Antifreeze & Coolant is a conventional green colored, low silicate antifreeze formulated for use in automotive, light-duty and heavy duty applications. Compatible with all conventional green colored antifreeze.



CHAMPION UNIVERSAL ANTIFREEZE

CHAMPION BRANDS Universal Antifreeze/Coolant is recommended, compatible, and formulated for use with ANY antifreeze/coolant in ANY vehicle with aluminum and other engine metals. Provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles.

ANTIFREEZE		Pkg.
4118AN	Permanent Antifreeze	55 Gal.
4118F	Permanent Antifreeze	6/1 Gal.
4119AN	Universal Antifreeze	55 Gal.
4119F	Universal Antifreeze	6/1 Gal.



WIPE-R-CLEAN® GLASS CLEANER

Safe and easy to use cleaner dissolves smudges, film, scum, smears, bugs and other soil. Excellent cleaner for windows, mirrors and other glass surfaces. This product is streakless and ammonia free.

4303P - 12 / 19 oz. (Is compliant for sale in North America)

FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT WWW.CHAMPIONBRANDS.COM

COMMERCIAL - INDUSTRIAL



FUEL STABILIZER

CHAMPION BRANDS FUEL STABILIZER is a concentrated formula designed for all 2 & 4 cycle engines. Keeps gasoline and diesel fuel fresh during storage and prevents corrosion and varnish build-up.



POWER STEERING FLUID

CHAMPION BRANDS POWER STEERING FLUID is a premium quality fluid designed for use in applications where the manufacturer specifies power steering fluid. Meets the performance requirements of major foreign, as well as domestic automobile makers.



ETHANOL TREATMENT

CHAMPION BRANDS eGUARD® ETHANOL FUEL TREATMENT has benefits that include the stabilization of fuel and removal of water. Ethanol Treatment also offers reduced gum formation.



FUEL INJECTOR CLEANER

CHAMPION BRANDS FUEL INJECTOR CLEANER keeps fuel injector systems clean, and cleans carburetors on older models. Maintains proper injector spray patterns. Helps remove water and contamination from fuel system.




DOT 4 BRAKE FLUID

CHAMPION BRANDS SYNTHETIC DOT 4 BRAKE FLUID provides the ultimate in high temperature protection, moisture resistance, and lubricity for ABS, hydraulic drum, disc braking systems, and hydraulic clutches.



OCTANE TREATMENT

CHAMPION BRANDS OCTANE TREATMENT is formulated to reduce the need for higher octane fuels. Great fuel stabilizer, and compatible with all gasoline additives. Oxygen sensor safe as well.



DOT 3 BRAKE FLUID

CHAMPION BRANDS DOT 3 BRAKE FLUID meets or exceeds Federal Motor Vehicle Safety Standards (FMVSS) No. 116 (DOT 3) and Society of Automotive Engineers (SAE) J1703 specifications.



AIR LOK® TIRE INFLATOR

CHAMPION BRANDS AIR LOK® Tire Inflator is designed to be used with any passenger car, truck, boat trailer, or almost any pneumatic type tire. Safe method for temporary tire repair. Safer than roadside tire changing and will not adversely affect balance.



AIR LOK® TIRE SEALANT

CHAMPION BRANDS AIR LOK® Tire Sealant is a heavy duty sealant specially formulated to aid in the repair and prevention of flat tires caused by punctures, pinches, slow leaks, rim leaks, and bead leaks.

CHAMPION® PRODUCTS		Pkg.
4205M	Fuel Stabilizer	12/ 8 oz.
B10	Oil Analysis Kit	Each
4207M	Ethanol Treatment	12/ 8 oz.
4054K	Champion Dot 4 Brake Fluid	12/12 oz.
4054AN	Champion Dot 4 Brake Fluid	55 Gal.
4057K	Champion Dot 3 Brake Fluid	12/12 oz.
4057H	Champion Dot 3 Brake Fluid	12/ 1 Qt.
4057D	Champion Dot 3 Brake Fluid	5 Gal.
4057F	Champion Dot 3 Brake Fluid	6/ 1 Gal.
4057AN	Champion Dot 3 Brake Fluid NR	55 Gal.
4086K	Champion AirLok w/nozzle Aero	12/ 12 oz.
4086KH	Champion AirLok w/hose Aero	12/ 12 oz.
4086I	Champion AirLok Tire Sealant	12/ 16 oz.
4086N	Champion AirLok Tire Sealant	4/ 1 Gal.
4182K	Champion Power Steering Fluid	12/ 12 oz.
4182H	Champion Power Steering Fluid	12/ 1 Qt.
4182N	Champion Power Steering Fluid	4/ 1 Gal.
4182AN	Champion Power Steering Fluid	55 Gal.
4186K	Honda Power Steering Fluid	12/12 oz.
4275K	Champion Fuel Injector Cleaner	12/ 12 oz.
4276K	Champion Octane Treatment	12/ 12 oz.
4183W	Champion A/S Diesel Flo	6/64 oz.

HONDA POWER STEERING FLUID

Full Synthetic Power Steering Fluid formulated to meet the specific performance demands required by all **2007 and newer** Honda/Acura power steering systems. Has a higher viscosity than conventional power steering fluids, which helps provide superior protection.



FOR CURRENT PRODUCT INFORMATION AND SPECIFICATIONS VISIT WWW.CHAMPIONBRANDS.COM



DIESEL FLO®

CHAMPION BRANDS DIESEL FLO® is a multi-functional diesel fuel additive that boosts performance in the key areas of injector detergency, fuel lubricity, fuel stability, corrosion protection, and cold flow improvement when used in ultra low sulfur (ULSD) and Bio-diesel (B5-B20) fuels.



About Champion

Champion Brands, LLC, originally Lowe Oil Co. founded by Ralph Lowe in 1956, is a globally recognized industry leader in specialty lubricants for over 55 years. Champion also produces and blends over 300 products including fuel, oil, engine additives, and lubricants for the racing, automotive, heavy truck, agricultural, industrial, and specialty markets.

Champion Brands understands the complexities of doing business in today's market and is always looking for new and better ways to make your company more efficient and increase your bottom line. Quality products are more than a commitment at Champion; our high standards define the way we do business.

For more information about Champion Commercial and Industrial Oils contact your nearest Champion Distributor, or call Champion at 800-821-5693. Champion Brands, LLC; 1001 Golden Drive, Clinton, MO, 64735 or visit our website at <http://www.championbrands.com>







COMMERCIAL & INDUSTRIAL

VISIT US AT

facebook 

You Tube
 Broadcast Yourself 

twitter 



**SCAN FOR:
 COMPANY INFO
 PRODUCT INFO
 TECH BULLETINS
 SAFETY DATA SHEETS**



For more information about Champion Brands and Champion Products go to:
ChampionBrands.com or ChampionsUseChampion.com

1-800-821-5693